

1294(1.6)
d:\work files\cam profiles\Pushrod Roller\R1294.CPP

		LIFT	DUR.	OPEN	CLOSE	AREA
Lobe	I1	---	---	---	---	---
Centerline	108.00 ATDC	0.004	297.20	38.10 BTDC	79.11 ABDC	28.00
Runout	0.00000	0.006	289.47	35.11 BTDC	74.35 ABDC	27.98
Lift @ TDC	0.0760	0.010	278.46	30.30 BTDC	68.16 ABDC	27.94
Valve Lash	0.0000	0.012	274.06	28.32 BTDC	65.75 ABDC	27.91
Rocker Ratio	1.60	0.014	270.09	26.51 BTDC	63.58 ABDC	27.89
Lobe Separation	110.0	0.016	266.55	24.91 BTDC	61.64 ABDC	27.86
Minimum Flat		0.018	263.33	23.46 BTDC	59.87 ABDC	27.83
Follower Dia.	0.9655	0.020	260.39	22.11 BTDC	58.28 ABDC	27.80
		0.040	239.10	12.85 BTDC	46.25 ABDC	27.49
		0.050	230.18	8.79 BTDC	41.39 ABDC	27.29
		0.100	198.16	6.84 ATDC	24.99 ABDC	26.11
		0.200	148.42	31.88 ATDC	0.30 ABDC	22.40
		0.300	87.43	62.59 ATDC	29.98 BBDC	14.66
		0.35083	---	PEAK CAM LIFT	---	
		0.56132	---	PEAK VALVE LIFT	---	

d:\work files\cam profiles\Pushrod Roller\R1294.CPP

		LIFT	DUR.	OPEN	CLOSE	AREA
Lobe	E1	---	---	---	---	---
Centerline	112.00 BTDC	0.004	301.46	76.48 BBDC	44.98 ATDC	27.99
Runout	0.00000	0.006	292.23	73.57 BBDC	38.66 ATDC	27.96
Lift @ TDC	0.0601	0.010	280.36	68.90 BBDC	31.46 ATDC	27.92
Valve Lash	0.0000	0.012	275.80	66.93 BBDC	28.87 ATDC	27.89
Rocker Ratio	1.60	0.014	271.73	65.17 BBDC	26.55 ATDC	27.87
Lobe Separation	110.0	0.016	268.09	63.59 BBDC	24.49 ATDC	27.84
Minimum Flat		0.018	264.85	62.16 BBDC	22.68 ATDC	27.81
Follower Dia.	0.9474	0.020	261.89	60.86 BBDC	21.03 ATDC	27.78
		0.040	238.94	50.45 BBDC	8.49 ATDC	27.45
		0.050	230.36	46.41 BBDC	3.95 ATDC	27.25
		0.100	198.34	30.84 BBDC	12.50 BTDC	26.08
		0.200	148.23	5.71 BBDC	37.49 BTDC	22.33
		0.300	86.97	25.42 ABDC	67.61 BTDC	14.56
		0.35028	---	PEAK CAM LIFT	---	
		0.56044	---	PEAK VALVE LIFT	---	